HALLMARK FLOORS®
HARDWOOD FLOORING

VENTURA COLLECTION
ENGINEERED HARDWOOD

Pier Oak

Mangrove Oak VE75MANO

Sandal Oak VE75SANO

Seashell Oak VE75SEAO

Marina Oak VE75MARO

Maritime Walnut VE75MARW

Pearl Oak VE75PEAO

Sandbar Hickory VE75SANH

White Cap Oak VE75WHIO

Dune Oak VE75DUNO

Pier Oak VE75PIEO

Wharf Oak VE75WHAO

Hampton Hickory VE75HAMH

Wharf Oak

HALLMARK FLOORS®
HARDWOOD FLOORING

VENTURA COLLECTION
ENGINEERED HARDWOOD

Features

Dimensions:	7½" x 6'2" RL
Thickness:	1/2" Engineered TrueCore Centerply 2mm Slice Cut Face
Finish:	Nu Oil® (Oak) TrueMark® Glaze Tek Poly (Walnut, Hickory)
Edge Detail:	Handcrafted Microbevel
Surface Texture:	Wire Brushed
Certified:	EPA – TSCA Title IV Compliant - Clean air Certified Renewable Sourcing
TrueCore:	Third Party Certified
Warranty:	Limited Lifetime residential finish Limited Lifetime residential structural 3 year commercial finish (Nu Oil®) 5 year commercial finish (Glaze Tek) 10 year commercial structural
Maintenance:	APPROVED CLEANERS: For Nu Oil®: WOCA Natural Soap Spray and Natural Soap Concentrate, Bona® Pro Series Natural Oil Floor Cleaner OR LOBA® Universal Floor Cleaner For Glaze Tek: WOCA Hardwood, LVT, Tile & Laminate Floor Cleaner, Bona® Pro Series Hardwood Floor Cleaner, OR LOBA® Universal Floor Cleaner

Dune Oak

Benefits

Finish:	Protective low sheen - provides a truly natural wood floor (Oak) Guaranteed quality and durability - long lasting finish
Wear Layer:	Wear layer provides lasting durability Same wear layer as 3/4 solid wood floors Easier to repair or touch up if an accident occurs
Structure:	75% Greater dimensional stability than 3/4" solid Healthy indoor air quality - Third party certified TrueCore centerply for maximum stability

Trim Options

Stair Nose
T-molding
Threshold
Reducer

Installation

Nail Down
Glue Down
Float
Over Radiant Heat (Excluding Hickory)

Installs over: concrete, wood, vinyl floors and radiant heat systems. Above, on or below grade. See complete installation instructions. Hallmark Hickory and Solid products are not approved for installation over Radiant Heat.

Refer to www.hallmarkfloors.com for latest, updated information.

TrueMark Glaze Tek Poly Finish
nu oil®
Truecore® Centerply

Fumed Characteristics

What to Expect with Fumed Floors

1. Regional Variation
2. Batch Variation
3. Plank Variation

Mangrove Oak, Sandal Oak, Seashell Oak, Marina Oak, Pearl Oak are Fumed.

Fuming simply deepens the natural colors and highlights the contrast of the wood planks without using stain to cover them. Our process creates a naturally richer, darker, clearer floor with a higher contrast of colors from board to board.

What is Fumed Hardwood?
This is a natural accelerated aging process used to enhance the dark to light shades within every wood plank, batch & region. The deepening in color and variation is created by adding a natural oxidizing agent in a controlled environment to react with the naturally present tannins in the wood – Time, Temperature & Tannins (naturally present in the wood) mix to create one of a kind planks that we add to our Collections. While a very controlled environment and process, it is not 100% precise, every region, grove and tree produces individually unique high contrast color palette.

Learn more about the beauty of fuming,
www.hallmarkfloors.com/the-beauty-of-fumed-hardwood-floors/

Wood Characteristics

Color, Graining & Natural Changes

Wood flooring is a natural product that will feature distinct color and graining between planks. Each board contains large to small knots, sap wood, and a high contrast within the natural and lighter stained visuals. Knots and voids may or may not be filled with dark putty.

Note: This sample may not be representative of your entire installed floor, for your reference and the latest updated information, please refer to hallmarkfloors.com to see our online room scenes and product galleries.

Before installation review the samples with the floor and verify our beautiful one of a kind floor is what you are expecting.

Installation constitutes acceptance.

Light Characteristics

Wood Floor Plank with Natural Finish
Light* Exposure Over 48 Months